

Oxydur-Flake B

218

: 05/03

xydur-Flake B

100°

160°

120°

1,45 / ²

40

100

22

24

6000

3,5 10⁻⁵ -1

15

25

1.

0,150 / ²

Steulerflake 25,0 1 . .

Oxydur Härter C 0,50 0,02 . .

2. **xydur-Flake B**

1 : 1,48

1,450 xydur-Flake B 1 . .

0,030 - Oxydur Härter C 0,02 . .

2

Verdüner M

(~100 / ²)

RAL7031 (~0,5% xydur-Flake B)

3.

0,245 Oxydur VE-U- 1,000 .

0,049 Beschleuniger D 0,020 . .

0,049 Oxydur Härter C 0,020 . .

Oxydur-Flake 3

Oxydur Härter C 12

25

210 . DIN 28053 DIN 28054,

020 021.

xydur-VE Laminat 1

450 .

70%.

Oxydur-Flake Steulerflake 25

xydur 1

/ ²

Oxydur-Flake B

	20						Pigmentpaste RAL 7031
	:			(0,5%	-)	
10	60	100					(3)
20	45	60					
25	20	40		10	,		
1)							
				2			6000
				3			9000
2)							
xydur-Flake B.				()	
		xydur-					
Oxydur VE-Laminat.				24		3	
10		450					xydur-Flake B
1			xydur-			1	
Flake B		Oxydur VE-Laminat.				24	
		24					
Oxydur VE-Laminat		Oxydur-Flake				3	
						24	
xydur-Flake B							
5	xydur-Flake B	100	Oxydur Härter C				xydur-Flake B
						10	
						24	
/ 2).	1		(1,45				
			Oxydur-Flake				15
	2					25	
	0,7		1 / 2				
			3				
	1	1,48 / 2					
			4				
0,75		1,05 / 2					
Verdünner M							
	! Verdünner M						
		xydur-Flake B.					