

Oxydur UP 410-Kunststofflaminat

410 .

410

70

410

DIN 53479 ASTM D297	1,42	/ ³
DIN 53455 ASTM C307	150	
DIN 53455 ASTM C307	150	
DIN 53455 ASTM C307	3	%
DIN 53457 ASTM C580	18000	
DIN 53452 ASTM C580	210	
DIN 53457 ASTM C580	11000	
DIN 53752 ASTM C531	2,6 · 10 ⁻⁵	- ¹

410 25,00
 425 1 3,00
 425 2 1,50
 20 0,30
 / ²
 425 0,25
 410 3,60
 -3 (450 / ²) 3,60 ²
 20 1,20 ²
 0,25
 4
 í î.
 2
 6
 : 20
 30

210 .
(
).

DIN 28052 2 3,
010 011.

Oxydur UP 410

DIN 28053 DIN 28054,
020 021.

70 425 2
70 20
: 300-400 / ²

33.

4% () 5%

70%.

2-3

1000 - /
20
60

20.

7030
300-400 / ²

425.

425 1 2
425 2 1
20 5-6%

5 24
20 12
35 5

7

4 , , 24

20

1 20. 410 : 70

190.

20.

2

4 , 12) (

10 . 12 4 ,

1000

410

STEULER
Industriewerke GmbH

