Oxidur-flake

Industriewerke GmbH

218

: 06/98

ISO EN DIN 9001 Zertifikat: 01 100 6383

:				- 1
•				- <u>2.</u>
	-	-	: 0,10 . 0,	
			: 0,36	
100°.			: 0,36 : 1,00	1
			20,00	0
	160°		60,00	- 20.
	120°		Ë	2
	120			
			: 1,00	
		1 45 / ²	20,00	0
		1, 10 /	60,00	20
()		40	1,20 2	450 / 2
		100		
		22	- , 1	·
		24	: 1,45	-
		6000 3.5.10 ⁻⁵ ⁻¹	14,5	0
		3,5 10 ⁻⁵ ⁻¹	87,0	- 20
		15		
		10	100 / 2 ;	
		25	RAL 7031 . 0,5%	
			- .	
			0.05	
		,	: 0,25	1
	, .		5,0	OF
	(-).	15,0	- 20
		<i>)</i> .	20 .	-
			15 , O (1%).
			407	(25)
,		,	1%	30 .
, ,	,	-		
	•			•
			-	3
				3
- :		25	0	6
0		250	-	12
- 20		300		, -
: .			25 .	

Oxidur-flake

```
20
                           DIN 28052
                                            1 2,
                      010 011.
                                                                   5
                                                                   300
                                                                                                 20 (1
                                                                                                                     ).
                   2.
           . DIN 28053 DIN 28054,
                                                                                                       48
            020 021.
4%.
                                                                   25
250
                                                                                      0
                                               60%.
                                                                                                     ).
                   3
                                                                   5
                                                                   300
                                                                                                20 (1
5
100
                                      1 - 100%
                           0
                               - 2%
300
                             20
                                           6%
                                                                                                                          1,45
                      20
                                  30
                                                                                         2
                              3
                                                                                0,7
    48
                                                                                                        3
                                                                                                   1,45 / 2
                                         20
                                                                                               1,05 / 2
                                                                           0,75
                                                                                                          (0,5%
                                  450 .
                  10
                      48
                                                                                                                       3
                                                                   10
                                                                       2
                                                                                                      6000
                                                                                                      9000
25
500
                     0
                                                                                                      (
Industriewerke GmbH
                                                                                                         ISO EN DIN 9001
Zertifikat: 01 100 6383
                                                      ),
```

Oxidur-flake



