



# INDUCRET-BIS 0/2 ( - 0/2)

5 50041

51/10

INDUCRET-BIS 0/2 – « »

- 6 25
- , 12
- 
- 
- 
- INDUCRET-BIS 0/2
- DIN EN ISO 12944-4 (
- 2,5).

INDUCRET-BIS 0/2 ( )

INDUCRET-BIS 0/2 – INDUCRET-BIS 5/40. 1,5

1. INDUCRET-BIS-0/2 25
  - 5,5 - 5,75
2. INDUCRET-BIS-0/2 25
  - 7,25 - 7,5

INDUCRET-BIS-0/2 ( 300 / ) 3

- 5 ) 2

24 ( - )

72 ( - )

1 0,5 1,2 / 3 60 20°C 1 +5 +35



INDUCRET-BIS 0/2

2

4

INDUCRET-BIS 0/2

INDUCRET-BIS 5/40

1,6 / 2/

1,0 / = 2,03

1,5 / 2/

1,0 / = 1,98 kg

INDUCRET-BIS 0/2

INDUCRET-BIS 0/2

INDUCRET-BIS 0/2.

° C - +35° C.

INDUCRET-BIS 0/2

INDUCRET-BIS

CC

	
<b>SCHOMBURG GmbH &amp; Co.KG</b> Aquafinstr. 2-8 D-32760 Detmold 08(1) 1119-CPD-0821	
EN 1504-3	
<b>INDUCRET-BIS 0/2</b>	
<b>INDUCRET-BIS CC</b>	
	R 4
	0,05 %
	2,0
	20
	2,0
	0,5 x <sup>-2</sup> x <sup>-0,5</sup>
	5.4

[www.elitstroy.su](http://www.elitstroy.su)

8 (495) 648-52-04

[mail@elitstroy.su](mailto:mail@elitstroy.su)

